

DAHUA IPC-HDW1439T1P-A-LED-0280B-S4 4 MP Entry Full-color Fixed-focal Eyeball Network kamera

Šifra: 12673
Kategorija proizvoda: IP Kamere
Proizvođač: DAHUA



Cena: 11.380,00 rsd.

	Automatski balans bele, Video tampering, Illegal access, BLC, HLC, Detekcija pokreta, WDR, 3D NR, ROI, voltage detection, privacy masking, Manual gain control, Smart Illumination, Image Rotation, Mirror, AGC, IP address conflict, Network disconnection, Ručni balans bele, BRC, Full-color, Alarm Event, Digital watermarking, Abnormality detection, Dannoć ColorBW		Dodatne
Snimanje:			
Mreža:	DMSS, ONVIF (Profile S&G&T), CGI, DSS, Smart PSS, API, SDK, P2P, Milestone		
	Dimenzije:	Φ109.9 mm x 85.5mm	
Fizičke karakteristike	Masa:	240g	
	Boja:	Bela	
	RAM:	128MB	
Memorija	Interna:	128MB	
	Podržane memorijske kartice:	NAS, FTP, SFTP	
Reklamacioni period	Reklamacioni period:	24 meseca	
	Tip kamere:	IP	
Senzor	Rezolucija senzora:	4 Megapiksela	
	Veličina:	1.280 x 720 (HD 720p), 1.920 x 1.080 (Full HD 1080p), 1.280 x 960 (1.3M), 704 x 576 (D1), 704 x 480 (D1), 640 x 480 (VGA), 352 x 288 (CIF), 352 x 240 (CIF), 2.304 x 1.296 (3M), 4M (2.560 × 1.440)	
Snimanje videa	Rezolucija videa:		
	Frame rate:	1~2530fps	
	Podržani video formati:	H.264, H.264B, H.265, MJPEG, Smart H.264+, Smart H.265+	
Sočivo	Fokusna daljina:	2.8mm	
	Fokusni koeficijent:	F1.6	
Zaštita	Ostalo:	802.1x, Video encryption, configuration encryption, Digest,	

WSSE, account lockout, security logs, Generation and importing of X.509 certification, HTTPS, trusted boot, trusted execution, trusted upgrade, Firmware encryption, IPMAC filtering, Syslog

Protok žične mreže:

RJ-45 (10/100Mbps Base-T)
IPv4, ARP, TCP, UDP, RTSP, RTP, RTCP, IPv6, HTTP, FTP, NTP, SMTP, DNS, DDNS, PPPOE, DHCP, UPnP, IGMP, QoS, Bonjour, Multicast, NFS, SFTP, RTMP

Protokoli:

Žična mreža