

DAHUA IPC-HDW1439T1P-LED-0280B-S4 4 MP Entry Full-color Fixed-focal Eyeball Network Camera

Šifra: 12681
Kategorija proizvoda: IP Kamere
Proizvođač: DAHUA

Cena: 11.380,00 rsd.



Dodatne

Snimanje:	Automatski balans bele, Video tampering, Illegal access, BLC, HLC, Detekcija pokreta, WDR, 3D NR, ROI, voltage detection, privacy masking, Manual gain control, Smart Illumination, Image Rotation, Mirror, AGC, IP address conflict, Network disconnection, Ručni balans bele, BRC, Full-color, Alarm Event, Digital watermarking, Abnormality detection, Dannoć ColorBW	
Mreža:	DMSS, ONVIF (Profile S&G&T), CGI, DSS, Smart PSS, API, SDK, P2P, Milestone	
Fizičke karakteristike	Dimenzije:	Φ109.9 mm x 85.5mm
	Masa:	240g
	Boja:	Bela
	RAM:	128MB
Memorija	Interna:	128MB
	Podržane memorijske kartice:	NAS, FTP, SFTP
Reklamacioni period	Reklamacioni period:	24 meseca
Senzor	Tip kamere:	IP
	Rezolucija senzora:	4 Megapiksela
	Veličina:	1,280 x 720 (HD 720p), 1.920 x 1.080 (Full HD 1080p), 1.280 x 960 (1.3M), 704 x 576 (D1), 704 x 480 (D1), 640 x 480 (VGA), 352 x 288 (CIF), 352 x 240 (CIF), 2.304 x 1.296 (3M), 4M (2.560 x 1.440)
	Rezolucija videa:	
Snimanje videa	Frame rate:	1~2530fps
	Podržani video formati:	H.264, H.264B, H.265, MJPEG, Smart H.264+, Smart H.265+
Sočivo	Fokusna daljina:	2.8mm
	Fokusni koeficijent:	F1.6
Zaštita	Ostalo:	802.1x, Video encryption, configuration encryption, Digest,

WSSE, account lockout, security logs, Generation and importing of X.509 certification, HTTPS, trusted boot, trusted execution, trusted upgrade, Firmware encryption, IPMAC filtering, Syslog

Protok žične mreže:

RJ-45 (10/100Mbps Base-T),
IPv4, ARP, TCP, UDP, RTSP, RTP,
RTCP, IPv6, HTTP, FTP, NTP,
SMTP, DNS, DDNS, PPPOE, DHCP,
UPnP, IGMP, QoS, Bonjour,
Multicast, NFS, SFTP, RTMP

Protokoli:

Žična mreža